

PWC 542418

FEATURES

Heavy-duty stainless steel construction

Handfinished with hemmed edges and welded seams

Blower required (internal, in-line or remote blowers available)

Recessed controls for sleeker look

Infinite speed blower control

Bright halogen lighting

Heat sentry for safety

Transition with backdraft minimizes backward flow of cold air

Install with accessory duct cover for chimney-style hood

Rigorously tested in our U.S. manufacturing facilities for decades of use

Exceptional 24/7 support from our Customer Care team in Madison

ACCESSORIES

38" high stainless steel backsplash with or without warming racks

6", 12", 18" and 24" high stainless steel duct covers

Make-up air damper

Accessories available through an authorized Sub-Zero dealer.
For local dealer information, visit subzero-wolf.com/locator.



BLOWER OPTIONS

- 300 CFM Internal
- 450 CFM Internal
- 600 CFM Internal
- 900 CFM Internal
- 1200 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- 600 CFM Remote
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote

PRODUCT SPECIFICATIONS

Model	PWC542418
Dimensions	54"W x 18"H x 24"D
Weight	106 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

NOTE:

Dimensions in parenthesis are in millimeters unless otherwise specified

DIMENSIONS